

## Certificate of Analysis

1.15333.0000 Water for chromatography (LC-MS Grade) LiChrosolv® Z0997033

	Batch Values	
Spec. conductance at 25 °C at the time of manufacturing)	≤ 1	μS/cm
Al (Aluminium)	≤ 10	ppb
Ca (Calcium)	≤ 100	ppb
Fe (Iron)	≤ 5	ppb
〈 (Potassium)	≤ 10	ppb
Mg (Magnesium)	≤ 20	ppb
Na (Sodium)	≤ 200	ppb
Any further metal (ICP-MS)	≤ 5	ppb
COC	≤ 30	ppb
Evaporation residue	≤ 5	mg/l
Fluorescence (as quinine at 254 nm)	≤ 1	ppb
Fluorescence (as quinine at 365 nm)	≤ 0.5	ppb
Gradient grade (at 210 nm)	≤ 5	mAU
Gradient grade (at 254 nm)	≤ 0.5	mAU
Gradient grade (basic absorption (210 nm))	≤ 20	mAU
	Batch Values	
Anions (IC)		nah.
Chloride (CI)	≤ 10	ppb
Chloride (CI) Nitrate (NO₃)	≤ 10 ≤ 10	ppb
Chloride (CI) Nitrate (NO₃) Phosphate (PO₄)	≤ 10 ≤ 10 ≤ 10	ppb
Chloride (CI) Nitrate (NO₃)	≤ 10 ≤ 10	ppb
Chloride (CI) Nitrate (NO₃) Phosphate (PO₄)	≤ 10 ≤ 10 ≤ 10 ≤ 10	ppb
Chloride (CI) Nitrate (NO₃) Phosphate (PO₄)	≤ 10 ≤ 10 ≤ 10	ppb
Chloride (CI) Nitrate (NO₃) Phosphate (PO₄)	≤ 10 ≤ 10 ≤ 10 ≤ 10	ppb
Chloride (CI) Nitrate (NO <sub>3</sub> ) Phosphate (PO <sub>4</sub> ) Sulfate (SO <sub>4</sub> ) Sulfate for LC-MS; Intensity of background mass peak based on reserpine	≤ 10 ≤ 10 ≤ 10 ≤ 10 Batch Values	ppb ppb ppb
Chloride (CI) Nitrate (NO <sub>3</sub> ) Phosphate (PO <sub>4</sub> ) Sulfate (SO <sub>4</sub> )  Suitable for LC-MS; Intensity of background mass peak based on reserpine APCI/ESI positive) Suitable for LC-MS; Intensity of background mass peak based on reserpine	≤ 10 ≤ 10 ≤ 10 ≤ 10 Batch Values	ppb ppb

Date of release (DD.MM.YYYY) 23.05.2025 Minimum shelf life (DD.MM.YYYY) 31.05.2028

Christian Herrmann

Responsible laboratory manager quality control

This document has been produced electronically and is valid without a signature.